

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860004 - LD-CC-1-10V-32

Leddriver constante stroom


/productimages/860004.jpg

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Dynamic
Output power (W)	2 - 32
(W)	2 - 15
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	2 - 53
Input voltage (V)	220 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	250 - 900
Yes	
(mA)	250
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	103
Width (mm)	67
Height (mm)	21
Rated frequency (Hz)	50 - 60
0.95	
Ambient temperature (°C)	-25 - +50
White	
No	
No	
(W)	32
1 - 13	
1 - 5	
1 - 4	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Kema certified	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Suitable for pulse button	Yes



Dimming 1-10 V	Yes
Dimming phase cut-on	No
Dimming DALI	No
Dimming DMX	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	No
Dimming 0-10 V	Yes
Dimming with push-button	Yes
No	