

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/860008.jpg

**Leddriver constante stroom**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Model	Dynamic
Output power (W)	1 - 38
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	10 - 54
Input voltage (V)	120 - 277
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	300 - 1050
Yes	
(mA)	1050
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	146.5
Width (mm)	44
Height (mm)	30
Rated frequency (Hz)	50 - 60
0.95	
Ambient temperature (°C)	-25 - +45
White	
No	
No	
3 - 16	
2 - 5	
2 - 5	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Dimmable	Yes
Operation by Bluetooth	Yes
Dimming DALI-2	No
Compatible with Casambi	Yes
Dimming potentiometer (integrated)	No
Suitable for pulse button	Yes
Dimming 1-10 V	No



Dimming phase cut-on	No
Dimming DALI	No
(%)	3 - 100
Dimming DMX	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	No
Dimming 0-10 V	No
Dimming with push-button	Yes