

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 860030 - LA-DRV-13W350PD

Leddriver constante stroom

/productimages/860030.jpg

Package type: BG á 1 pce



**PRODUCT SPECIFICATIONS:**

Protocol	Phase cut-off
Model	Dynamic
Output power (W)	6 - 13
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	18 - 38
Input voltage (V)	198 - 264
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	350 - 350
No	
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	120
Width (mm)	53
Height (mm)	27
Rated frequency (Hz)	50 - 60
0.95	
Max. starting current (A)	5
Ambient temperature (°C)	-20 - +55
White	
No	
5 - 11	
2 - 4	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
Dimming potentiometer (integrated)	No
Dimming 1-10 V	No
Dimming phase cut-on	No
Dimming DALI	No
(%)	10 - 100
Dimming DMX	No
Constant light output (CLO)	No



Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	Yes
Dimming 0-10 V	No