

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/860084.jpg


**Leddriver constante stroom**

Package type: BG á 1 pce



**PRODUCT SPECIFICATIONS:**

|  |                 |
|--|-----------------|
| Model                                  | Dynamic         |
| Output power (W)                       | 5.5 - 10        |
| Housing                                | Plastic housing |
| Suitable for constant voltage          | No              |
| Output voltage (V)                     | 7 - 14          |
| Input voltage (V)                      | 220 - 240       |
| Suitable for DC-voltage (primary side) | No              |
| Suitable for constant current          | Yes             |
| Output current (mA)                    | 700 - 700       |
| No                                     |                 |
| Degree of protection (IP)              | IP20            |
| Suitable for outdoor use               | No              |
| Length (mm)                            | 110             |
| Width (mm)                             | 47              |
| Height (mm)                            | 32              |
| Rated frequency (Hz)                   | 50 - 60         |
| 0.95                                   |                 |
| Max. starting current (A)              | 5               |
| Ambient temperature (°C)               | 10 - 45         |
| White                                  |                 |
| No                                     |                 |
| 3 - 4                                  |                 |
| 1 - 1                                  |                 |
| Frequency input voltage (Hz)           | 50 - 60         |
| Independently operating                | Yes             |
| Yes                                    |                 |
| Overload protection                    | Yes             |
| Yes                                    |                 |
| Overtemperature protection             | Yes             |
| Yes                                    |                 |
| Yes                                    |                 |
| No                                     |                 |
| None                                   |                 |
| Operation by Bluetooth                 | No              |
| Dimming DALI-2                         | No              |
| Compatible with Casambi                | No              |
| Dimming potentiometer (integrated)     | No              |
| Dimming 1-10 V                         | No              |
| Dimming phase cut-on                   | No              |
| Dimming DALI                           | No              |
| (%)                                    | 10 - 100        |
| Dimming DMX                            | No              |



|                             |    |
|-----------------------------|----|
| Constant light output (CLO) | No |
| Dimming Touch and Dim       | No |
| Dimming DSI                 | No |
| Dimming Zigbee              | No |
| Dimming phase cut-off       | No |
| Dimming 0-10 V              | No |