

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/860224.jpg

Leddriver constante spanning

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Protocol	Zigbee
Model	Dynamic
Output power (W)	1 - 50
Housing	Plastic housing
Suitable for constant voltage	Yes
Output voltage (V)	24 - 24
Input voltage (V)	110 - 277
Suitable for DC-voltage (primary side)	No
Suitable for constant current	No
No	
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	210
Width (mm)	60
Height (mm)	32
Rated frequency (Hz)	50 - 60
Ambient temperature (°C)	-20 - +45
White	
No	
No	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
Short-circuit protected	Yes
No	
None	
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	No
Dimming LineSwitch	No
Dimming phase cut-on	No



Dimming DALI	No
Dimming programmable	Yes
Dimming Sine Wave Reduction	No
Dimming DMX	No
Dimming mains voltage modulation	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	Yes
Dimming phase cut-off	No
Dimming 0-10 V	No
Dimming with push-button	No