

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/860230.jpg


**Leddriver constante stroom**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Protocol	Zigbee
Model	Dynamic
Output power (W)	1 - 38
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	10 - 54
Input voltage (V)	220 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	300 - 1050
Yes	
(mA)	1050
Degree of protection (IP)	IP20
Protection class	II
Suitable for outdoor use	No
Length (mm)	146.5
Width (mm)	44
Height (mm)	30
Rated frequency (Hz)	50 - 60
0.95	
Ambient temperature (°C)	-20 - +45
(%)	3
White	
No	
No	
4 - 16	
2 - 5	
2 - 5	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
Short-circuit protected	Yes
No	
Efficiency (%)	90
None	
Max. number of luminaires per miniature circuit breaker B16	50



Dimmable	Yes
PWM modulation	No
Operation by Bluetooth	No
Dimming DALI-2	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Suitable for pulse button	Yes
Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	No
Dimming LineSwitch	No
Dimming phase cut-on	No
Dimming DALI	No
Dimming programmable	Yes
Dimming Sine Wave Reduction	No
Dimming DMX	No
Dimming mains voltage modulation	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	Yes
Dimming phase cut-off	No
Dimming 0-10 V	No
Dimming with push-button	Yes