

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

860300 - LD-MINI-4-350D

Leddriver constante stroom

876804.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Protocol	Phase cut-off
Model	Static
Output power (W)	2.1 - 4
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	6 - 12
Input voltage (V)	198 - 264
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	350 - 350
No	
Degree of protection (IP)	IP20
Protection class	II
Suitable for outdoor use	No
Length (mm)	48
Width (mm)	30
Height (mm)	20
Rated frequency (Hz)	50 - 60
0.9	
Max. starting current (A)	5
Ambient temperature (°C)	-20 - +60
White	
Yes	
Number of channels	1
1 - 1	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
Short-circuit protected	Yes
No	
Efficiency (%)	68
(kV)	1
(kV)	0.5
None	
Max. number of luminaires per miniature circuit breaker B16	224
Max. number of luminaires per miniature circuit breaker C16	400
(h)	50000



Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
IFTTT support available	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Compatible with Apple HomeKit	No
Suitable for pulse button	No
Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	No
Dimming LineSwitch	No
Dimming phase cut-on	No
Dimming DALI	No
Dimming programmable	No
Dimming Sine Wave Reduction (%)	8 - 100
Dimming DMX	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	Yes
Dimming 0-10 V	No
Dimming with push-button	No