

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

863199 - DL-LUNA2W-EWW

LED Downlighters

Package type: CT á 1 pce

/productimages/863199.jpg



PRODUCT SPECIFICATIONS:

| | |
|---|---|
| Mounting method | Built-in |
| Colour temperature (K) | 2700 - 2700 |
| Colour of light adjustable | No |
| Nominal current (mA) | 110 - 700 |
| Nominal voltage (V) | 36 - 36 |
| Voltage type | DC |
| Max. system power (W) | 26 |
| Beam angle | Extreme wide beam >80° |
| Beam angle (°) | 120 |
| Built-in depth (mm) | 107 |
| Height/depth (mm) | 134 |
| Outer diameter (mm) | 173 |
| Built-in diameter (mm) | 162 - 162 |
| Housing colour | White |
| Degree of protection (IP), front side | IPX0 |
| IP20 | |
| Suitable for ceiling mounting | Yes |
| Luminous flux adjustable | Continuously variable |
| Suitable for lamp power (W) | 1 - 26 |
| Adjustability | not adjustable |
| Lamp type | LED not exchangeable |
| With light source | Yes |
| Electrical connection with connector system | Yes |
| Type of control gear | LED operating device current-controlled |
| With control gear | No |
| Colour of light | White |
| Housing material | Aluminium |
| Light sharing | Symmetric |
| Colour rendering index CRI | 80-89 |
| Suitable for built-in mounting | Yes |
| Optics | Reflector |
| No | |
| (cm) | 100 |
| Number of poles | 2 |
| Colour consistency (McAdam ellipse) | SDCM1 |
| Exchangeable control gear | Yes |
| With presence indicator | No |
| Dimmable | Yes |