

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/863201.jpg

LED Downlighters

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Mounting method	Built-in
Colour temperature (K)	3000 - 3000
Colour of light adjustable	No
Nominal current (mA)	110 - 700
Nominal voltage (V)	36 - 36
Voltage type	DC
Max. system power (W)	26
Beam angle	Extreme wide beam >80°
Beam angle (°)	120
Built-in depth (mm)	107
Height/depth (mm)	134
Outer diameter (mm)	173
Built-in diameter (mm)	162 - 162
Housing colour	White
Degree of protection (IP), front side	IPX0
IP20	
Suitable for ceiling mounting	Yes
Luminous flux adjustable	Continuously variable
Suitable for lamp power (W)	1 - 26
Adjustability	not adjustable
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	No
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	80-89
Suitable for built-in mounting	Yes
Optics	Reflector
No	
(cm)	100
Number of poles	2
Colour consistency (McAdam ellipse)	SDCM1
Exchangeable control gear	Yes
With presence indicator	No
Dimmable	Yes