

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

868167 - LM-BTSP26W-30EWW

Lumiko modulair B-trackspots

Package type: CT á 1 pce

/productimages/868167.jpg



PRODUCT SPECIFICATIONS:

Colour temperature (K)	2700 - 2700
Colour of light adjustable	No
Nominal current (mA)	0 - 700
Nominal voltage (V)	230 - 230
Voltage type	AC
Max. system power (W)	26
Energy efficiency class of the light source according to EU regulation 2019/2015	E
Beam angle	Medium beam 21-40°
Beam angle (°)	30
Length (mm)	107
Width (mm)	148
Height/depth (mm)	140
(mm)	90
Outer diameter (mm)	90
Housing colour	Black
Degree of protection (IP), front side	IPX0
IP20	
Suitable for lamp power (W)	26 - 26
Suitable for light-track mounting	Yes
Adjustability	Rotating and swivelling
Lamp type	LED not exchangeable
With light source	Yes
Electrical connection with connector system	Yes
Type of control gear	LED operating device current-controlled
With control gear	Yes
Colour of light	White
Housing material	Aluminium
Light sharing	Symmetric
Colour rendering index CRI	90-100
Optics	Lens
Suitable for low voltage cable system	No
Yes	
Surface protection	Powder coating
Surface brushed	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming phase cut-on	No
Light distributor	Focal lens
Light outlet	Direct

Number of poles	3
Connection type	Busbar adapter
Colour consistency (McAdam ellipse)	SDCM2
With mounting bracket	No
With presence indicator	No
Dimming manufacturer's proprietary system	No
Dimmable	Yes
Dimming phase cut-off	Yes
Dimming 0-10 V	No
Dimming DMX	No
Dimming DALI-2	No