

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870476.jpg

**Aanwezigheidsdetector Universeel**

Package type: CT á 1 pce



## PRODUCT SPECIFICATIONS:

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Animal zone	No
Integrated	
Relay	
Networkable	No
Suitable for wall mounting	Yes
Optimum mounting height (m)	2.5
Max. reach sideways (m)	4.5
(VA)	800
Max. reach frontally (m)	2.5
Diameter reach on floor (m)	9
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Response value luminosity adjustable	Yes
Teach-function for response value luminosity	Yes
Dim function with dimmer basic element	No
Max. mounting height (m)	3
Material	Plastic
Material quality	Thermoplastic
Colour	Black
RAL-number (similar)	9005
Transparent	No
Degree of protection (IP)	IP55
Voltage type	AC
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Yes	
Detection angle horizontal (°)	5 - 360
(mm)	65
Response value luminosity (lx)	10 - 2000
Max. switching power (W)	2300
Built-in size (mm)	68
Number of switching zones	1
Max. starting current (A)	800
Frequency (Hz)	50 - 60
Scan angle (°)	360

Max. presence range (m <sup>2</sup> )	65
Suitable for ceiling mounting	Yes
Connection type	Screwed terminal
With connection cable	No
Anti-bacterial treatment	No
Width (mm)	105
Height (mm)	48
Diameter (mm)	105
Built-in depth (mm)	43.5
Built-in diameter (mm)	68
Max. switching power LED (W)	600
Compatible with Apple HomeKit	No
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	220 - 240
(V)	220 - 240
Yes	
(m)	12
(m <sup>2</sup> )	65
(m <sup>2</sup> )	113
6	
Yes	
No	
Yes	
Compatible with Casambi	No