

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870480.jpg

**Aanwezigheidsdetector Universeel**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Animal zone	No
Integrated	
Relay	
Networkable	No
Suitable for wall mounting	No
Optimum mounting height (m)	2.5
(VA)	800
Max. reach frontally (m)	3
Diameter reach on floor (m)	24
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Response value luminosity adjustable	Yes
Teach-function for response value luminosity	Yes
Dim function with dimmer basic element	No
Max. mounting height (m)	2.5
Material	Plastic
Material quality	Thermoplastic
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP55
Voltage type	AC
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Yes	
(mm)	43.5
Response value luminosity (lx)	10 - 2000
Max. switching power (W)	2300
(W)	0.5
Built-in size (mm)	68
Number of switching zones	1
Frequency (Hz)	50 - 60
Scan angle (°)	360
Max. presence range (m <sup>2</sup> )	465
Suitable for ceiling mounting	Yes



Connection type	Screwed terminal
With connection cable	No
Anti-bacterial treatment	No
Width (mm)	105
Height (mm)	79
Diameter (mm)	105
Built-in depth (mm)	44.5
Built-in diameter (mm)	68
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	220 - 240
(V)	220 - 240
Yes	
(m)	24
(m <sup>2</sup> )	465
(st)	2
10 - 2000	
Yes	
No	
Yes	
Compatible with Casambi	No