

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

/productimages/870540.jpg

**Bewegingsmelder inbouw**

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Model	Movement sensor
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	No
Forced switch off	Yes
Animal zone	No
Integrated	
Relay	
Networkable	No
Suitable for wall mounting	Yes
Optimum mounting height (m)	1.2
Staircase monitoring	No
Max. reach sideways (m)	8
(VA)	300
Diameter reach on floor (m)	8
(W)	200
Suitable for wireless transmission	No
Remote operation	No
2	
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	1600
With signal unit	No
Teach-function for response value luminosity	Yes
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	1.5
Material	Plastic
Material quality	Thermoplastic
Surface finishing	Glossy
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP40
Voltage type	AC
Min. switch-on time (s)	5
(mm)	80
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 180
Response value luminosity (lx)	5 - 10000



Max. switching power (W)	1600
(W)	0.6
Number of switching zones	1
Frequency (Hz)	50 - 60
Scan angle (°)	180
Suitable for ceiling mounting	No
Connection type	Screwed terminal
With connection cable	No
Width (mm)	80
Height (mm)	80
Depth (mm)	24
Built-in width (mm)	50
Built-in depth (mm)	32
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	220 - 240
1 make contact (NO)	
No	
2	
5 - 10000	
Yes	
No	
No	
Compatible with Casambi	No