

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870555.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Networkable	No
Suitable for wall mounting	No
Optimum mounting height (m)	2.5
Diameter reach on floor (m)	7
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP20
Detection angle horizontal (°)	1 - 360
(mm)	50
(m)	10
Built-in size (mm)	65
Number of switching zones	1
Scan angle (°)	360
Max. presence range (m ²)	165
Connection type	Other
With connection cable	Yes
Width (mm)	80
Height (mm)	15
Diameter (mm)	80
Built-in depth (mm)	38
Built-in diameter (mm)	65
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
No	
(st)	5



No



Yes

Compatible with Casambi

No

