

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870585.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
RJ11	
Networkable	No
Suitable for wall mounting	No
Optimum mounting height (m)	2.5
Diameter reach on floor (m)	10
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP40
Detection angle horizontal (°)	1 - 360
(mm)	50
(m)	10
Built-in size (mm)	65
Number of switching zones	1
Scan angle (°)	360
Max. presence range (m ²)	315
Suitable for ceiling mounting	Yes
Connection type	Other
With connection cable	Yes
Built-in diameter (mm)	65
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Yes	
(st)	2
No	
Yes	



Compatible with Casambi

No

