

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870642.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Presence detector
Passive infrared	
Constant light control	Yes
HVAC-control	No
DALI	
Networkable	No
Suitable for wall mounting	No
Optimum mounting height (m)	2.5
Bridging switch	Yes
Max. reach sideways (m)	6
Diameter reach on floor (m)	12
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
Teach-function for response value luminosity	Yes
Dim function with dimmer basic element	Yes
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP54
Voltage type	AC
Min. switch-on time (s)	60
Max. duty cycle (min)	60
(mm)	49
Response value luminosity (lx)	10 - 2000
Yes	
(W)	0.5
Built-in size (mm)	67
Number of switching zones	2
Frequency (Hz)	50 - 60
Scan angle (°)	360
Max. presence range (m ²)	460
Suitable for ceiling mounting	Yes



Connection type	Screwed terminal
With connection cable	No
Width (mm)	80
Height (mm)	15
Diameter (mm)	80
Built-in width (mm)	67
Built-in depth (mm)	49
Built-in diameter (mm)	67
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	220 - 240
(V)	220 - 230
Yes	
(m)	16
(m ²)	120
(m ²)	200
10 - 2000	
Yes	
No	
Yes	
Compatible with Casambi	No