

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/870880.jpg

Aanwezigheidsdetector Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Presence detector
High frequency	
Constant light control	No
HVAC-control	Yes
Forced switch off	Yes
Networkable	No
Optimum mounting height (m)	2.5
Max. reach sideways (m)	10
(VA)	200
Diameter reach on floor (m)	10
Suitable for wireless transmission	No
Remote operation	No
10	
With remote control	No
Response value sensitivity adjustable	Yes
Response value luminosity adjustable	Yes
(W)	1000
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP20
Voltage type	AC
Min. switch-on time (s)	5
(mm)	90
Max. duty cycle (min)	30
Detection angle horizontal (°)	1 - 360
Response value luminosity (lx)	5 - 1000
No	
Max. switching power (W)	1000
Number of switching zones	1
Frequency (Hz)	50 - 60
Scan angle (°)	360
Max. presence range (m ²)	50
Suitable for ceiling mounting	Yes
Connection type	Screwed terminal
With connection cable	No



Width (mm)	51
Height (mm)	31.5
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	230 - 230
1 make contact (NO)	
Yes	
(m ²)	80
No	
Compatible with Casambi	No