

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870470.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Model	Presence detector
Passive infrared	
Technique	Passive infrared
Constant light control	No
HVAC-control	Yes
Networkable	No
Suitable for wall mounting	No
Optimum mounting height (m)	2.5
Max. reach sideways (m)	12
Max. reach frontally (m)	3
Diameter reach on floor (m)	24
Suitable for wireless transmission	No
Remote operation	Yes
With remote control	No
Response value luminosity adjustable	Yes
(W)	2300
Mounting method	Flush mounted (plaster)
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Transparent	No
Degree of protection (IP)	IP54
Voltage type	AC
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Yes	
(mm)	43.5
Response value luminosity (lx)	10 - 2000
No	
Max. switching power (W)	2300
(W)	0.5
Built-in size (mm)	68
Number of switching zones	1
Frequency (Hz)	50 - 60
Scan angle (°)	360
Max. presence range (m ²)	465
Suitable for ceiling mounting	Yes
Connection type	Other
With connection cable	Yes

Width (mm)	105
Height (mm)	44.5
Diameter (mm)	105
Built-in depth (mm)	43.5
Built-in diameter (mm)	68
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	230 - 230
(V)	230 - 230
Yes	
(m)	24
(m ²)	465
(m ²)	465
6	
10 - 2000	
Yes	
No	
Yes	
Compatible with Casambi	No