

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 871472 - PIR-SMART-3,2M

Package type: CT á 1 pce

**PRODUCT SPECIFICATIONS:**

Model	Presence detector
Passive infrared	
Constant light control	No
HVAC-control	No
Forced switch off	No
Animal zone	Yes
Integrated	
Relay	
Networkable	Yes
Suitable for wall mounting	No
Optimum mounting height (m)	3
Staircase monitoring	Yes
Bridging switch	No
Max. reach sideways (m)	8.3
(VA)	800
Max. reach frontally (m)	8.3
(W)	600
Suitable for wireless transmission	No
Remote operation	No
25	
With remote control	No
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
(W)	2000
Teach-function for response value luminosity	Yes
Dim function with dimmer basic element	No
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	4
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9016
Transparent	No
Degree of protection (IP)	IP20
Voltage type	AC
Min. switch-on time (s)	30
Max. duty cycle (min)	30
Detection angle horizontal (°)	5 - 360
(mm)	65
Response value luminosity (lx)	10 - 2000
Max. switching power (W)	2000



Built-in size (mm)	63
Number of switching zones	1
Max. starting current (A)	800
Substation input	No
Frequency (Hz)	50 - 60
With alarm function	No
Scan angle (°)	360
Max. presence range (m <sup>2</sup> )	68.3
Suitable for ceiling mounting	Yes
Connection type	Screwed terminal
With connection cable	No
Anti-bacterial treatment	No
Width (mm)	80
Height (mm)	5
Diameter (mm)	80
Built-in depth (mm)	67
Built-in diameter (mm)	63
Max. switching power LED (W)	600
Compatible with Apple HomeKit	No
Yes	
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Nominal voltage (V)	220 - 240
Yes	
6	
Yes	
No	
Yes	
Compatible with Casambi	No
Ambient temperature (°C)	-10 - +40