

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

870470.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

Model	Presence detector
Technique	Passive infrared
Constant light control	Yes
HVAC-control	No
Forced switch off	No
Optimum mounting height (m)	2.5
Max. reach sideways (m)	15
(VA)	2300
Max. reach frontally (m)	15.75
Diameter reach on floor (m)	15
Remote operation	No
30	
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	12
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Degree of protection (IP)	IP41
Min. switch-on time (s)	14
Max. duty cycle (min)	840
Detection angle horizontal (°)	1 - 360
(mm)	70
Response value luminosity (lx)	5 - 10000
Yes	
(W)	3
Built-in size (mm)	45
Control current (mA)	10
Frequency (Hz)	50 - 60
Yes	
Nominal voltage (V)	230 - 230
(V)	230 - 230
No	
(m ²)	39.2
(m ²)	235.5