

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/871520.jpg

Aanwezigheidsdetector Plafond Inbouw

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Model	Presence detector
Technique	Passive infrared
Constant light control	Yes
HVAC-control	No
Forced switch off	No
Optimum mounting height (m)	2.5
Max. reach sideways (m)	7.2
Max. reach frontally (m)	9
Diameter reach on floor (m)	7
Remote operation	No
Response value sensitivity adjustable	No
Response value luminosity adjustable	Yes
Mounting method	Flush mounted (plaster)
Max. mounting height (m)	5
Material	Plastic
Material quality	Thermoplastic
Surface protection	Lacquered
Surface finishing	Matt
Colour	White
RAL-number (similar)	9010
Degree of protection (IP)	IP41
Voltage type	AC
Detection angle horizontal (°)	1 - 360
(mm)	70
Response value luminosity (lx)	5 - 10000
Yes	
Max. switching power (W)	2300
Built-in size (mm)	45
Max. starting current (A)	800
Frequency (Hz)	50 - 60
Yes	
Nominal voltage (V)	230 - 230
(V)	230 - 230
1 make contact (NO)	
No	