

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

## 876361 - LR-AD-CAS-W-31

**Leddriver constante stroom**

/productimages/876361.jpg

Package type: CT á 1 pce



**PRODUCT SPECIFICATIONS:**

Model	Dynamic
Output power (W)	14 - 31
Housing	Plastic housing
Suitable for constant voltage	No
Output voltage (V)	20 - 44
Input voltage (V)	220 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	325 - 700
Yes	
(mA)	700
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	228
Width (mm)	32
Height (mm)	43
Rated frequency (Hz)	50 - 60
0.97	
Ambient temperature (°C)	-20 - +35
White	
No	
No	
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Operation by Bluetooth	No
Compatible with Casambi	Yes
Dimming potentiometer (integrated)	No
Dimming 1-10 V	No
Dimming phase cut-on	No
Dimming DALI	No
Dimming DMX	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	No



Dimming 0-10 V

No

