

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

876399 - LR-AD-CAS-ZW-31

Leddriver constante stroom

876361.jpg

Package type: CT á 1 pce

PRODUCT SPECIFICATIONS:

| | |
|--|-----------------|
| Model | Dynamic |
| Output power (W) | 14 - 31 |
| Housing | Plastic housing |
| Suitable for constant voltage | No |
| Output voltage (V) | 20 - 44 |
| Input voltage (V) | 220 - 240 |
| Suitable for DC-voltage (primary side) | No |
| Suitable for constant current | Yes |
| Output current (mA) | 325 - 700 |
| Yes | |
| (mA) | 700 |
| Degree of protection (IP) | IP20 |
| Suitable for outdoor use | No |
| Length (mm) | 228 |
| Width (mm) | 32 |
| Height (mm) | 43 |
| Rated frequency (Hz) | 50 - 60 |
| Ambient temperature (°C) | -20 - +35 |
| White | |
| No | |
| No | |
| Frequency input voltage (Hz) | 50 - 60 |
| Independently operating | Yes |
| Yes | |
| Overload protection | Yes |
| Yes | |
| Overtemperature protection | Yes |
| Yes | |
| Yes | |
| No | |
| None | |
| Operation by Bluetooth | No |
| Compatible with Casambi | Yes |
| Dimming potentiometer (integrated) | No |
| Dimming 1-10 V | No |
| Dimming phase cut-on | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Constant light output (CLO) | No |
| Dimming Touch and Dim | No |
| Dimming DSI | No |
| Dimming Zigbee | No |
| Dimming phase cut-off | No |
| Dimming 0-10 V | No |

