

Klemko Techniek B.V.
Phone: +31 (0)880023300
E-mail: info@klemko.nl

klemko®

/productimages/876808.jpg

Leddriver universeel

Package type: CT á 1 pce



PRODUCT SPECIFICATIONS:

Protocol	1 - 10 V
Model	Dynamic
Output power (W)	1 - 20
Housing	Plastic housing
Suitable for constant voltage	Yes
Output voltage (V)	6 - 42
Input voltage (V)	180 - 240
Suitable for DC-voltage (primary side)	No
Suitable for constant current	Yes
Output current (mA)	150 - 1200
Yes	
(mA)	700
Degree of protection (IP)	IP20
Suitable for outdoor use	No
Length (mm)	110
Width (mm)	52
Height (mm)	24
Rated frequency (Hz)	50 - 60
0.9	
Ambient temperature (°C)	-20 - +45
Grey	
Yes	
1 - 8	
1 - 12	
1 - 4	
1 - 3	
(m)	5.5
Frequency input voltage (Hz)	50 - 60
Independently operating	Yes
Yes	
Overload protection	Yes
Kema certified	Yes
Yes	
Overtemperature protection	Yes
Yes	
Yes	
No	
None	
Dimmable	Yes
Operation by Bluetooth	No
Dimming DALI-2	No
IFTTT support available	No



Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
Dimming potentiometer (integrated)	No
Compatible with Apple HomeKit	No
Suitable for pulse button	Yes
Dimming RF	No
Dimming manufacturer's proprietary system	No
Dimming 1-10 V	Yes
Dimming LineSwitch	No
Dimming phase cut-on	No
Dimming DALI	No
Dimming programmable	No
Dimming Sine Wave Reduction (%)	0 - 100
Dimming DMX	No
Dimming mains voltage modulation	No
Constant light output (CLO)	No
Dimming Touch and Dim	No
Dimming DSI	No
Dimming Zigbee	No
Dimming phase cut-off	No
Dimming 0-10 V	No