

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

891038.jpg

Package type: CT á 1 pce

**PRODUCT SPECIFICATIONS:**

Assembly arrangement	Basic element
Method of operation	Turn/push button
Serial dimmer	No
Protocol	Phase cut-off
Type of load	Universal and LED Retrofit
Substation input	Yes
Light value memory	Yes
Applicable with button	No
Applicable with movement sensor	Yes
Applicable with presence indicator	Yes
Applicable with time switch/timer	Yes
Applicable with transmission button	No
Applicable with infrared button	No
Mounting method	Flush mounted (plaster)
Type of fastening	Mounting with screw
Material	Other
Material quality	Aluminium
Halogen free	Yes
Surface protection	Untreated
Surface finishing	Glossy
Colour	Aluminium
Transparent	No
Suitable for degree of protection (IP)	IP20
Nominal voltage (V)	207 - 253
Frequency (Hz)	50 - 50
Device width (mm)	71
Device height (mm)	71
Device depth (mm)	22
App control via Bluetooth	No
Dimming phase cut-on	No
Dimming phase cut-off	Yes
Nominal power resistive load (W)	3 - 500
Nominal power capacitive load (VA)	3 - 500
Connection type	Push-in clamp
Core cross section (mm <sup>2</sup> )	1.5 - 2.5
Min. depth of built-in installation box (mm)	25
Max. switching power LED (W)	500
Min. brightness controllable	Yes