

Klemko Techniek B.V.  
Phone: +31 (0)880023300  
E-mail: info@klemko.nl

# klemko®

891042.jpg

Package type: CT á 1 pce

**PRODUCT SPECIFICATIONS:**

|  |                            |
|--|----------------------------|
| Assembly arrangement                         | Basic element              |
| Method of operation                          | Configuration dependant    |
| Serial dimmer                                | No                         |
| Protocol                                     | Phase cut-off              |
| Type of load                                 | Universal and LED Retrofit |
| Substation input                             | No                         |
| Light value memory                           | Yes                        |
| Applicable with button                       | Yes                        |
| Applicable with movement sensor              | Yes                        |
| Applicable with presence indicator           | Yes                        |
| Applicable with time switch/timer            | Yes                        |
| Applicable with transmission button          | No                         |
| Applicable with infrared button              | No                         |
| Mounting method                              | Flush mounted (plaster)    |
| Type of fastening                            | Mounting with screw        |
| Material                                     | Other                      |
| Material quality                             | Aluminium                  |
| Halogen free                                 | Yes                        |
| Surface protection                           | Untreated                  |
| Surface finishing                            | Glossy                     |
| Colour                                       | Aluminium                  |
| Transparent                                  | No                         |
| Suitable for degree of protection (IP)       | IP20                       |
| Nominal voltage (V)                          | 207 - 253                  |
| Frequency (Hz)                               | 50 - 50                    |
| Device width (mm)                            | 71                         |
| Device height (mm)                           | 71                         |
| Device depth (mm)                            | 22                         |
| App control via Bluetooth                    | Yes                        |
| Dimming phase cut-on                         | No                         |
| Dimming phase cut-off                        | Yes                        |
| Nominal power resistive load (W)             | 3 - 300                    |
| Nominal power capacitive load (VA)           | 3 - 300                    |
| Connection type                              | Push-in clamp              |
| Core cross section (mm <sup>2</sup> )        | 1.5 - 2.5                  |
| Min. depth of built-in installation box (mm) | 25                         |
| Max. switching power LED (W)                 | 300                        |
| Brand-dependent                              |                            |
| Min. brightness controllable                 | Yes                        |